


TVI C200



The TVI C200 video encoder has been specifically designed to meet the exacting requirements of our customers.

The compact, low power unit enables high quality real-time, low latency video to be viewed over narrow bandwidth networks including GPRS and 3G telecoms networks, satellite networks, tactical IP radios and the Internet with quality, reliability and usability unmatched by standards based products.

At the heart of the system is the secure server application, enabling multiple encoders and viewers to work together securely and seamlessly to create a fully scalable architecture. Using wireless technology the system can be deployed in minutes avoiding the delays and costs associated with installing fixed line communications. The system provides access to video feeds by decision makers anywhere without the need for fixed infrastructure. Video streams can also be played on wireless devices such as PDAs while maintaining exceptional clarity, and full PTZ control of cameras at the viewer end gives the system maximum flexibility. With user definable frame rates and frame sizes, the TVI video encoder can be configured to match your specific operational requirements. Where bandwidth is fundamentally limited, Hawkeye technology offers the only useable solution to live video transmission with high quality, real-time video.

KEY POINTS

- *Lightweight, compact enclosure with no moving parts for reliable, silent operation*
- *True real-time video over narrow bandwidths – operates at 9 Kbps to 1 Mbps*
- *Maintains constant frame rate without exceeding bandwidth limits*
- *Low latency for accurate PTZ control*
- *Supports two way audio*
- *High Resolution Image Retrieval with simultaneous streaming of video*
- *Low power requirement - nominal 6 watts, 0.1 watt sleep mode*
- *Wide operational temperature range -32° to +60°, non-condensing*
- *Multiple viewers in different locations can view live video streams simultaneously*
- *AES 256 Encryption*



TVI C200



KEY POINTS

• Form factor

The unit is designed to be as light and compact as possible, with no moving parts for silent operation. Small enough to be easily portable, the unit is constructed to accommodate the high level of vibration associated with vehicle deployment.

• Communications

In addition to standard LAN and ADSL, Satellite connectivity for Inmarsat GAN/BGAN Fleet Routers is available via the RJ45 Ethernet connector. The system is network agnostic, so there are no restrictions on which network you can use.

• Configuration

The unit is configured via USB key pen, and subsequent configuration or upgrades can be applied remotely. A useful feature of the software ensures that the previous configuration is always stored locally and is therefore available should configuration update fail for any reason.

• Power

One of the key features of the unit is low power, with a nominal figure of 5.5 watts. This will reduce further when using lower frame rates.

An additional feature of the system is a standby mode, sub 1.5 watts, plus a sleep mode effectively reducing the power requirement to 0.1 watt when not actively in use. The unit can be set to wake up after a pre-defined interval or can be woken by an external trigger.

• Archiving

The unit can be fully integrated with a standard DVR. This will allow multiple video inputs to be archived to the DVR, with the archived video accessible for viewing remotely using our specific viewer software.

TVI C200 TECHNICAL SPECIFICATION

Hardware

Physical Size: L 195mm x W 148mm x D 37mm*, Weight 700g	Camera Input: 1 x BNC composite input
Operating Temperature: -32° to +60°, non-condensing	Video Input Format: PAL / NTSC / SECAM
Audio: Stereo Audio In / Stereo Audio Out	1 Alarm Input: Triggers at 5V (24V max)
Input Voltage: 9V-36V DC	Power Consumption: 7W max 5.5W nominal <1.5W Standby mode <0.1W Sleep mode

*Dimensions include connectors

Front Panel Connectors



USB Configuration of the unit is via USB. The USB connector also allows connection to serial based devices	LEDs Status LEDs provide information on start up and configuration.
RJ45 RJ45 Ethernet connector for ADSL and network lines.	

